



RAVENOL VSG SAE 75W-90



1L | 1221101-001
4L | 1221101-004
10L | 1221101-010
20L | 1221101-020
20L | 1221101-B20
60L | 1221101-060
60L | 1221101-D60
208L | 1221101-208
208L | 1221101-D28
1000L | 1221101-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221101

Specification: API GL-4, API GL-5

Oil type: Fully synthetic

Recommendation: BMW 83222365987, BMW 83229407768, BMW OSP, BMW SAF-XO, BOT 130 M, BOT 328, BOT 720, DAF LKW (für verlängerte Intervalle), Ford 1045737, Ford 5021033, Ford WSD-M2C200-C, IVECO, Land Rover TYK500010, MAN 342 S1, MB 235.11, MB 235.8, MIL-L-2105 D, Porsche 000.043.305.04, Porsche 958.341.536.00 (Torsen 2010-2018), Renault LKW, Scania STO 1:0, VOLVO 97312, VOLVO 97315, VOLVO 97319, VW G 052 145 A2, VW G 052 539 A2, VW G 052 911 A2, ZF TE-ML 12B, ZF TE-ML 16F, ZF TE-ML 17B

Application: Passenger car, Truck, Agricultural machinery

RAVENOL VSG SAE 75W-90 is a high performance universal transmission oil based on fully synthetic components.

RAVENOL VSG SAE 75W-90 is designed based on high-quality synthetic base oils with a special additive treatment and inhibition ensuring trouble-free transmission function.

Application Note

RAVENOL VSG SAE 75W-90 is excellent for use of highly stressed axle drives.

RAVENOL VSG SAE 75W-90 is suitable for synchronised and non-synchronised manual transmissions, transfer cases and ancillary transmission requiring API GL-5 or GL-4 oil.

Characteristics

- high additive reserves for prolonged oil change intervals according to the manufacturer specifications
- excellent cold flow properties
- best wear protection and best transmission efficiency Fuel savings even with short distances in low outdoor temperatures
- stable lubricating film even under high stress
- extraordinary corrosion protection and good compatibility with non-ferrous metal
- high oxidation resistance prevents oil thickening and deposits
- outstanding dirt-carrying capacity, i.e. aggregates are clean even after very long oil change intervals
- excellent elastomer compatibility to prevent leaks
- extreme shearing stability, remains within the clean oil viscosity per SAE class 75W-90 even after very long periods of use
- very high protection from rust, corrosion and foaming
- extreme low pour point
- excellent EP properties
- fuel savings

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	840,0	EN ISO 12185
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	16,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	108,8	DIN 51562-1
Viscosity Index VI		168	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	47.000	ASTM D2983
Pourpoint	°C	-57	DIN ISO 3016
Flashpoint	°C	226	DIN EN ISO 2592
Seq. I at 24 °C	ml/ml	0/0	ASTM D892
Seq. II at 93,5 °C	ml/ml	0/0	ASTM D892
Seq. III at 24 °C after 93,5 °C	ml/ml	0/0	ASTM D892
Copper Strip Test at 121 °C		1a	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.

10.07.2022