



RAVENOL MTF-1 SAE 75W-85

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221102

Specification: API GL-4, API GL-5

Oil type: Fully synthetic

Recommendation: GM 1940182, GM 93740319, Hyundai 04300-00110, Hyundai 04300-00140, Hyundai 08950-00020-A, Hyundai 08950-00020-B, MB 235.4 (A 001 989 14 03), Mitsubishi 3717610, MTF BOT 0063 für F35/MU3 5-speed SAAB/GM/Opel, MTF BOT 402, Nissan 999MP-MTF00P, Nissan KE91699931, Nissan KE91699942, Nissan KLD26-75802, Opel/GM B0402071, Toyota 08885-02606, Toyota 08885-81060, Toyota 08885-81070

Application: Passenger car



RAVENOL MTF-1 SAE 75W-85 is a PAO based fully synthetic, low-viscosity transmission oil for special manual transmissions, transfer cases and differential gears.

RAVENOL MTF-1 SAE 75W-85 is designed based on special selected base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL MTF-1 SAE 75W-85 is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

Application Note

RAVENOL MTF-1 SAE 75W-85 is high-performance gear oil for manual transmission, transfer cases and differential gears.

Characteristics

- Excellent thermal stability.
- High protection from rust, corrosion, foaming.
- Low solidification point.
- Excellent EP properties.
- Good shifting behavior in low temperatures.
- Extended life.
- Fuel savings.

1L | 1221102-001

4L | 1221102-004

10L | 1221102-010

20L | 1221102-020

20L | 1221102-B20

60L | 1221102-060

60L | 1221102-D60

208L | 1221102-208

208L | 1221102-D28

1000L | 1221102-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	855,0	EN ISO 12185
Colour		rot	VISUELL
Brookfield Viscosity at -40 °C	mPa*s	52.400	ASTM D2983
Pourpoint	°C	-42	DIN ISO 3016
Copper Strip Test at 121 °C		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.

10.07.2022